13245X/98 2000W 400V

Product family description

Tubular double-ended infrared halogen lamp used as highpower and high-efficiency heat source for various industrial applications

Product Features

High efficiency

Product Benefits

- · Instant heat: full power within I second at switching on
- Clean: no by product and no pollution emitted by Infrared lamps
- Safe: heat shock resistant lamp thanks to its quartz envelop
- Economical: more than 85% of the consumed energy is transmitted into infrared heat
- Fully dimmable: Infrared lamps are accurately controllable (0% to 100%)
- Possibility to put sensor: On/Off switches do not affect life time of Infrared lamps
- Low maintenance: long life time of about 5 000 hours
- Heat can be focused: Infrared lamps have the same optical properties as light, meaning that the heat can be directed by reflectors

Application

- Paint drying in tunnels and body shops
- Blowing of PET bottles
- · Plastics thermoforming
- Softening, melting of plastics
- Epitaxy, CVD, RTP, Oxidation processes in semiconductor industry
- · Heating of food and keeping it warm
- · Paper drying
- · Drying of lacquer, printing inks
- · Heat sterilization

| Product data | | | | |
|-------------------|----------------------|--|--|--|
| Product Number | 312520 | | | |
| Full product name | 13245X/98 2000W 400V | | | |
| Ordering Code | 312520 | | | |




| Product data | | | | | | |
|--------------------------|----------------|--|--|--|--|--|
| Pack type | Unpacked | | | | | |
| Pieces per Sku | 1 | | | | | |
| Skus/Case | 10 | | | | | |
| Pack UPC | 8711500214706 | | | | | |
| EAN2US | | | | | | |
| Case Bar Code | 8711500510747 | | | | | |
| Successor Product number | | | | | | |
| Cap-Base | X | | | | | |
| Bulb | TII | | | | | |
| Bulb Finish | Reflector | | | | | |
| Operating Position | p15 | | | | | |
| Main Application | Industrial | | | | | |
| Packing Type | UNP [Unpacked] | | | | | |
| Packing Configuration | 10 | | | | | |
| Life to 50% failures | 5000 hr | | | | | |
| Pack UPC | 8711500214706 | | | | | |
| Case Bar Code | 8711500510747 | | | | | |
| Ordering Code | 13245X/98 | | | | | |
| Watts | 2000W | | | | | |
| Beam Description | FA180 | | | | | |
| Overall Length C | 508 mm | | | | | |
| Diameter D | | | | | | |
| Case Height | 3.000 in | | | | | |
| Case Length | 28.000 in | | | | | |
| Case Width | 12.000 in | | | | | |
| Product Number | 312520 | | | | | |
| Pack Height | 1.000 in | | | | | |
| Pack Length | I.000 in | | | | | |
| Pack Weight | 0.300 in | | | | | |
| Pack Width | 1.000 in | | | | | |

XHIRINDR X

no image available








Cap-Base X



Operating Position p15







XHIRINDR X

| | A | A | С | С | D | D |
|------------------------------------|-----|-----|-----|-----|-----|-----|
| Full produc t name | Nom | Nom | Max | Max | Max | Max |
| 13245 X/98 2000 W 400V | 410 | 410 | 508 | 508 | П | П |

Full product name
13245×/98 2000W 400V



$@2009\ Koninklijke\ Philips\ Electronics\ N.V.$

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liablity will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Document order number : 0000 000 00000