

ITT 2000 W 235 V-0826 K/S

HALOTHERM | Infrared halogen lamps with white reflector



Areas of application

- Manufacture of PET bottles
- Coil coating
- Professional grills and heated counters in restaurants

Product benefits

- High efficiency
- Precise controllability
- Long lamp life
- Short response time

Product features

- Short-wave infrared halogen lamps (IR-A) for technical applications
- Maximum radiation at a wavelength of about 1,100 nm



Product datasheet

Technical data


Electrical data

Nominal wattage	2000.00 W
Nominal voltage	235 V
Construction voltage	235.00 V
Lamp current	8.5 A
Nominal current	8.5 A

Photometrical data

Color temperature	2350 K
-------------------	--------

Dimensions & weight



Diameter	10.0 mm
Length	351.0 mm
Filament length	285.00 mm
Cable length	200.0 mm

Lifespan

Lifespan	5000 h
----------	--------

Additional product data

Base (standard designation)	K9x15/21
Connector: Presence	Yes
Product remark	Cable length 600 mm

Capabilities

Burning position	Any
------------------	-----

Product datasheet

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321206350	OSRHALOTT2000KS	-	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321206350	ITT 2000 W 235 V-0826 K/S	Folding carton box 1	378 mm x 26 mm x 26 mm	0.26 dm ³	82.00 g
4008321206367	ITT 2000 W 235 V-0826 K/S	Shipping carton box 12	395 mm x 90 mm x 125 mm	4.44 dm ³	1030.00 g
4008321259790	ITT 2000 W 235 V-0826 K/S	Shipping carton box 1	- x - x -		
4008321259806	ITT 2000 W 235 V-0826 K/S	Shipping carton box 60	660 mm x 455 mm x 285 mm	85.59 dm ³	12520.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.