
SIG 1260

Low-voltage over-pressure single-coil lamps, railway



Areas of application

- Railway traffic signalling systems

Product benefits

- Narrow geometrical tolerances for safe operation of the signal installation
- Exact light centre position for optimum adjustment in the equipment
- Long lamp lifetime for efficient operation of signalling systems
- High reliability to avoid expensive delays to train schedules

Product datasheet

Technical data



Electrical data

Nominal wattage	20.0 W
Nominal voltage	10.0 V
Test voltage	10 V

Photometrical data

Nominal luminous flux	240 lm
-----------------------	--------

Dimensions & weight



Diameter	36.0 mm
Overall length	62.0 mm
Light center length (LCL)	33.5 mm ¹⁾

¹⁾ Distance from the coil to the lug of base

Lifespan

Nominal lamp life time	6000 h ¹⁾
------------------------	----------------------

¹⁾ Average lifespan at test voltage/current

Additional product data

Base (standard designation)	BA15s
Product remark	Available on request/Not for new designs

Capabilities

Burning position	Any ¹⁾
------------------	-------------------

¹⁾ Lamps with transverse filaments should only be inclined perpendicular to the filament plane

Country specific categorizations

Product datasheet

Order reference	SIG 1260UE CL 2
------------------------	-----------------

Product datasheet

Safety advice

Use only in equipment/luminaires that are specially designed for the purpose.
Protect the lamps against moisture during operation and installation.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300832036	SIG 1260	Unpacked 1	195 mm x 79 mm x 80 mm	1.23 dm ³	170.00 g
4050300233079	SIG 1260	Folding carton box 10	83 mm x 82 mm x 192 mm	1.31 dm ³	176.00 g
4050300233086	SIG 1260	Shipping carton box 100	411 mm x 172 mm x 206 mm	14.56 dm ³	1760.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
