

---

## SIG 64004

SIRIUS | Low-voltage halogen lamps with dichroic reflector, road traffic

---

### Areas of application

- Road and rail traffic signals



---

### Product benefits

- Fixed adjustment of halogen tube to reflector provides high luminous intensity
- Nearly constant luminous intensity due to high quality reflector coating
- Very long life due to the halogen tube

---

### Product features

- Connecting cables equipped with contacts/insulation widely resistant to corrosion and heat

# Product datasheet

## Technical data

### Electrical data

Nominal wattage	50.0 W
Nominal voltage	10.0 V
Test voltage	10 V


### Photometrical data

Nominal luminous flux	350 lm
-----------------------	--------

### Light technical data

Focal length	42.0 mm
Aperture window, maximum	10.2 mm

### Dimensions & weight



Diameter	51.0 mm
Base diameter	24.5 mm
Overall length	46.5 mm
Cable length	105.0 mm

### Lifespan

Nominal lamp life time	2000 h <sup>1)</sup>
------------------------	----------------------

<sup>1)</sup> Average lifespan at test voltage/current

### Additional product data

Base (standard designation)	K23d
-----------------------------	------

### Capabilities

Burning position	p90
------------------	-----

# Product datasheet

## Country specific categorizations

<b>Order reference</b>	SIG 64004 CL 50
------------------------	-----------------

---

## Country specific information


<b>Product code</b>	<b>METEL code</b>	<b>SEG number</b>	<b>STK number</b>	<b>UK Org</b>
4050300245225	OSRSIG64004HC	8334878	4730152	-

## Product datasheet

---

### Safety advice

All halogen signal lamps operate at high temperature and pressure. They may therefore only be operated in signal equipment/luminaires specially designed for the purpose. Make sure that the lamps are protected against moisture during operation and in particular during relamping.



---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300245225	SIG 64004	Folding carton box 1	53 mm x 52 mm x 52 mm	0.14 dm <sup>3</sup>	46.60 g
4050300245232	SIG 64004	Shipping carton box 10	268 mm x 63 mm x 114 mm	1.92 dm <sup>3</sup>	516.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.